



ProSeries™

Top-Mount Sand Filters

CORROSION RESISTANT CONSTRUCTION
FOR LONG LASTING PERFORMANCE



EXPERT LINE



ONLY FROM POOL PROS



3+ YEAR WARRANTIES



PARTS & LABOR COVERAGE

*When sold by a Totally Hayward® Partner. Exclusions, other terms and conditions may apply — visit hayward.com/expert for details.

PROSERIES™ TOP-MOUNT FEATURES

- » **Integral top diffuser** ensures even distribution of water over the sand media bed. Full-size internal piping provides smooth, free-flowing performance
- » **Flanged clamp design** allows for 360° valve rotation to simplify plumbing
- » **Efficient multilateral underdrain assembly** with precision-engineered, self-cleaning 360° slotted laterals provides totally balanced flow and backwashing
- » **Integral molded drain plug** drains the tank without losing sand
- » **Unitized, corrosion-proof tank** is molded of color-fast polymeric material for maximum all-weather durability
- » **Corrosion-proof base** provides strong, stable support
- » **Patented service-ease design** with unique folding ball joint provides easy access to lateral assembly



7-position VariFlo® control valve with easy-to-use lever-action handle lets you dial any of 7 valve/filter functions.

SPECIFICATIONS

Filter Type	High-Rate Sand: No. 20 Silica Sand (0.45 mm–0.55 mm)	
Filter Tank	Molded Polymeric	
Underdrain	360° self-cleaning slotted laterals, precision installed in ball-joint assembly	
Valve Fastening	Flange Clamp Design	
Support Base	Injection-Molded Polymer	
Performance Range	30 to 120 GPM (114 to 454 LPM)	
	DIMENSIONS	CONTROL VALVE OPTIONS
Top-Mount	S220T – 22½"W x 41"H (572 mm x 1041 mm) S244T – 24½"W x 42"H (622 mm x 1067 mm) S220T2 – 22½"W x 41"H (572 mm x 1041 mm) S244T2 – 24½"W x 42"H (622 mm x 1067 mm) S270T – 27"W x 43"H (675 mm x 1075 mm) S270T2 – 27"W x 43"H (675 mm x 1075 mm) S310T2 – 30½"W x 48"H (775 mm x 1219 mm)	SP0714T – 1½" FIP 7-position, VariFlo SP071621 – 2" FIP 6-position, VariFlo

PERFORMANCE DATA

MODEL NUMBER	EFFECTIVE FILTRATION AREA	DESIGN FLOW RATE**	TURNOVER		SAND REQUIRED
			8 HOURS	10 HOURS	
S220T	2.64 ft. ² / 0.246 m ²	52 GPM / 197 LPM	24,960 gal / 94.47 kl	31,200 gal / 118.09 kl	250 lbs. / 114 kg
S220T2	2.64 ft. ² / 0.246 m ²	52 GPM / 197 LPM	24,960 gal / 94.47 kl	31,200 gal / 118.09 kl	250 lbs. / 114 kg
S244T	3.14 ft. ² / 0.292 m ²	62 GPM / 235 LPM	29,760 gal / 112.64 kl	37,200 gal / 140.80 kl	300 lbs. / 136 kg
S244T2	3.14 ft. ² / 0.292 m ²	62 GPM / 235 LPM	29,760 gal / 112.64 kl	37,200 gal / 140.80 kl	300 lbs. / 136 kg
S270T*	3.70 ft. ² / 0.345 m ²	74 GPM / 285 LPM	35,520 gal / 134.49 kl	44,400 gal / 168.07 kl	350 lbs. / 159 kg
S270T2*	3.70 ft. ² / 0.345 m ²	74 GPM / 285 LPM	35,520 gal / 134.49 kl	44,400 gal / 168.07 kl	350 lbs. / 156 kg
S310T2	4.91 ft. ² / 0.457 m ²	98 GPM / 371 LPM	47,040 gal / 178.05 kl	58,800 gal / 222.56 kl	500 lbs. / 227 kg

*Not NSF listed

**Based upon 20 GPM/ft.² 814 LPM/m² (Maximum Allowable NSF Rating)

» hayward.com » 1-888-HAYWARD

Pumps » Filters » Heating » Cleaners » Sanitization » Automation » Lighting » Water Features » White Goods

Hayward, Hayward & Design, and the H logo, and VariFlo are registered trademarks and ProSeries is a trademark of Hayward Industries, Inc. All other trademarks not owned by Hayward are the property of their respective owners. Hayward is not in any way affiliated with or endorsed by those third parties. © 2024 Hayward Industries, Inc.

LITPROTM05S24

 **HAYWARD®**
We Build Better.™